


## Conductivity Sensors

### High Pressure / Temperature 2 Electrode Conductivity Sensor 250 PSIG @ 205°C - 500 PSIG @ 100°C (Drawing 2P0072)

CS41	SS 316 / PCTFE (Kel-F) 3/4" MNPT Inline Sensor												
													
<b>Cell Constant (True range is analyzer/electrode size dependant)</b>													
<table border="1"> <tr> <td>2</td> <td>2.00 (0-30,000 MicroSiemens)</td> </tr> <tr> <td>1</td> <td>1.00 (0-20,000 MicroSiemens)</td> </tr> <tr> <td>0.1</td> <td>0.10 (0-1000 MicroSiemens)</td> </tr> <tr> <td>0.05</td> <td>0.05 (0-500 MicroSiemens)</td> </tr> </table>						2	2.00 (0-30,000 MicroSiemens)	1	1.00 (0-20,000 MicroSiemens)	0.1	0.10 (0-1000 MicroSiemens)	0.05	0.05 (0-500 MicroSiemens)
2	2.00 (0-30,000 MicroSiemens)												
1	1.00 (0-20,000 MicroSiemens)												
0.1	0.10 (0-1000 MicroSiemens)												
0.05	0.05 (0-500 MicroSiemens)												
<b>Pressure / Temperature Option</b>													
<table border="1"> <tr> <td>HT</td> <td>High Temp. 0 to 205°C, PEEK Insulator</td> </tr> <tr> <td>HV</td> <td>High Temp, Press, 6.5" OAL for use in 546 Hi-pressure insertion system</td> </tr> </table>						HT	High Temp. 0 to 205°C, PEEK Insulator	HV	High Temp, Press, 6.5" OAL for use in 546 Hi-pressure insertion system				
HT	High Temp. 0 to 205°C, PEEK Insulator												
HV	High Temp, Press, 6.5" OAL for use in 546 Hi-pressure insertion system												
<b>Integral Temperature Compensation</b>													
<table border="1"> <tr> <td>HW</td> <td>8550 Ohm @ 25°C (Honeywell)</td> </tr> <tr> <td>Pt100</td> <td>100 Ohm @ 0°C, PTC (BAT and Others)</td> </tr> <tr> <td>Pt1000</td> <td>1000 Ohm @ 0°C, PTC (BAT and Others)</td> </tr> </table>						HW	8550 Ohm @ 25°C (Honeywell)	Pt100	100 Ohm @ 0°C, PTC (BAT and Others)	Pt1000	1000 Ohm @ 0°C, PTC (BAT and Others)		
HW	8550 Ohm @ 25°C (Honeywell)												
Pt100	100 Ohm @ 0°C, PTC (BAT and Others)												
Pt1000	1000 Ohm @ 0°C, PTC (BAT and Others)												
<table border="1"> <tr> <td>1</td> <td>1.0" Insertion depth (standard)</td> </tr> <tr> <td>2.6</td> <td>2.6" Insertion depth for (HV) only</td> </tr> </table>						1	1.0" Insertion depth (standard)	2.6	2.6" Insertion depth for (HV) only				
1	1.0" Insertion depth (standard)												
2.6	2.6" Insertion depth for (HV) only												
<b>Cable</b>													
<table border="1"> <tr> <td>JB</td> <td>Junc Bx, Expl Proof, Inc 8" Ids &amp; Term Strip</td> </tr> <tr> <td>PT</td> <td>8" Pig Tail, for Cust Supp Junc Bx Inc Term Strip</td> </tr> <tr> <td>Coup</td> <td>3/4" coupling on rear of sensor</td> </tr> </table>						JB	Junc Bx, Expl Proof, Inc 8" Ids & Term Strip	PT	8" Pig Tail, for Cust Supp Junc Bx Inc Term Strip	Coup	3/4" coupling on rear of sensor		
JB	Junc Bx, Expl Proof, Inc 8" Ids & Term Strip												
PT	8" Pig Tail, for Cust Supp Junc Bx Inc Term Strip												
Coup	3/4" coupling on rear of sensor												
CS41	0.1	HT	PT100	1	JB								